





緊急停止ボタン

緊急停止

緊急停止

3.7 kW	4 POLE	TYPE	TFO
		FORM	K
VOLTS	200 200 220	RATING	CONT.
HERTZ	50 60 60	INSULATION	E
RPM	1440 1720 1730	AMB. TEMP.	40°C
AMPS	14.5 14 13	PROTECTION	JP44
JIS C	4210 4004	BRG. D.S.	6306UU
		BRG. O.S.	6306UU

Hitachi, Ltd. MFG. NO.
Tokyo Japan

2504890







2	1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20	21
22	23	24	25	26	27	28	29	30	31	



3.71W
400E 400E
175 200 250 300 350 400
175 200 250 300 350 400
175 200 250 300 350 400



























自動起動



入



切



7-711111













FUSE FREE BREAKER

S-100S 3P

TYPE	NO. OF POLES	AMP. CAP.
1	3	75A
2	3	75A
3	3	75A
4	3	75A
5	3	75A
6	3	75A
7	3	75A
8	3	75A
9	3	75A
10	3	75A
11	3	75A
12	3	75A
13	3	75A
14	3	75A
15	3	75A
16	3	75A
17	3	75A
18	3	75A
19	3	75A
20	3	75A
21	3	75A
22	3	75A
23	3	75A
24	3	75A
25	3	75A
26	3	75A
27	3	75A
28	3	75A
29	3	75A
30	3	75A
31	3	75A
32	3	75A
33	3	75A
34	3	75A
35	3	75A
36	3	75A
37	3	75A
38	3	75A
39	3	75A
40	3	75A
41	3	75A
42	3	75A
43	3	75A
44	3	75A
45	3	75A
46	3	75A
47	3	75A
48	3	75A
49	3	75A
50	3	75A
51	3	75A
52	3	75A
53	3	75A
54	3	75A
55	3	75A
56	3	75A
57	3	75A
58	3	75A
59	3	75A
60	3	75A
61	3	75A
62	3	75A
63	3	75A
64	3	75A
65	3	75A
66	3	75A
67	3	75A
68	3	75A
69	3	75A
70	3	75A
71	3	75A
72	3	75A
73	3	75A
74	3	75A
75	3	75A
76	3	75A
77	3	75A
78	3	75A
79	3	75A
80	3	75A
81	3	75A
82	3	75A
83	3	75A
84	3	75A
85	3	75A
86	3	75A
87	3	75A
88	3	75A
89	3	75A
90	3	75A
91	3	75A
92	3	75A
93	3	75A
94	3	75A
95	3	75A
96	3	75A
97	3	75A
98	3	75A
99	3	75A
100	3	75A

SERIAL NO. J 91

PROTECTOR LINE

1000000000

ON 75

OFF





